

**ARCHITECTURAL & ENGINEERING SPECIFICATION**

Exposed, quiet diaphragm-type, chrome-plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered bypass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

**PRODUCT FEATURES**

- Proprietary dezincification resistant low lead brass alloy
- Control stop has internal siphon-guard protection and vandal resistant stop cap, sweat solder kit, wall flange with set screw
- High back pressure vacuum breaker with one piece hex coupling nut
- Chloramine resistant internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

**COMPLIANCE AND CERTIFICATION:**

- Complies with ASSE 1037 / ASME A112.1037 / CSA B125.37
- ADA Compliant



This product should be used with a WaterSense labeled counterpart with a compatible flow volume to ensure that the entire system meets the requirements for water efficiency and performance.

**VALVE HEIGHT OPTIONS**

	DIMENSION A INCH [MM]
<b>-STANDARD</b>	11 1/2" [292]
<b>-1</b>	16" [406]
<b>-2</b>	24" [610]
<b>-3</b>	27" [686]

**Z6000AV ZURN ONE SYSTEMS**

Complete fixture package with bowl, flush valve, seat and trim

ITEM NUMBER	DESCRIPTION	FLUSH VOLUME GPF
<b>Z.WC1.M</b>	Wall Hung System	1.1
<b>Z.WC2.M</b>	Wall Hung System	1.28
<b>Z.WC3.M</b>	Standard Height Floor Bowl System	1.1
<b>Z.WC3.AM</b>	ADA Height Floor Bowl System	1.1
<b>Z.WC4.M</b>	Standard Height Floor Bowl System	1.28
<b>Z.WC4.AM</b>	ADA Height Floor Bowl System	1.28
<b>Z.WC5.M</b>	14" Floor Bowl System	1.28

**FLOW OPTIONS**

	FLUSH VOLUME GPF	DUAL FLUSH GPF	WATERSENSE COMPLIANT
<b>-ONE*</b>	1.1		☑
<b>-HET*</b>	1.28		☑
<b>-WS1</b>	1.6	1.6/1.1	
<b>-STANDARD</b>	3.5	3.5/2.4	

\* Not available with triple filter bypass

**SUFFIX OPTIONS**

- BG BioCare ADA Handle
- DF Dual Flush (See Chart Above)
- H Handle on Front of Flush Valve
- L 1" [25mm] Metal Push Button
- YJ Split Ring Pipe Support
- YK Solid Ring Pipe Support

**ARCHITECTURAL & ENGINEERING APPROVAL**

The information contained in this document is subject to change without notice.  
Please contact Zurn for most up to date information.

## Rough-in / Overview dimensions

